

## OVA

- Non see-through
- Installation friendly

### APPLICATION ▼

---

OVA is designed for use as a transfer and extract air unit. The grille is non see-through, and does not require an accurately dimensioned groove.

#### Design

OVA consist of a frame and fixed blades. Pre-drilled mounting holes are provided in the frame.

### DESCRIPTION ▼

---

#### Materials and surfaces

The grille is made in extruded aluminium, and comes in a RAL 9003 - gloss 30 finish. Alternative colours are available on request.


### INSTALLATION ▼

---

OVA is mounted by means of countersunk plate screws in the grille frame. Number of screws required is included. 2 for widths up to and incl. 400, and 4 for widths of 500 and 600.

## TECHNICAL INFORMATION

### ORDER CODE, OVA



Example:  
OVA-300-200 / 0  
Explanation:  
OVA - Width: 300, Height: 200

 QUICK SELECTION

OVA Dim.	[m <sup>3</sup> /h]		
	10 Pa	15 Pa	20 Pa
200-100	58	72	83
300-100	112	137	155
300-150	184	223	263
300-200	252	306	360
400-100	144	176	205
400-150	223	270	317
400-200	288	353	403
500-150	245	299	349
500-200	360	443	504
500-250	461	547	648
500-300	540	666	792
600-200	414	511	594
600-300	666	810	954
600-400	882	1062	1224