



## RIA-SA

### LOUVRE FOR CENTRAL EXTRACT SYSTEM

- For high air flow rates
- Available in standard white, RAL 9003 - gloss 30

#### APPLICATION □

---

RIA-SA is an extract-air louvre ideal for high air flow rates.

##### **Design**

RIA-SA is made from extruded aluminium profiles.

#### DESCRIPTION □

---

##### **Materials and surfaces**

RIA-SA is made from extruded, seawater resistant aluminium profiles (ENAW-6060-T66 / EN-AW-6063-T6), and comes in an RAL 9003 - gloss 30 finish as standard. The unit can also be delivered in anodized brown, black or natural. Alternative materials or enamel finish are available on request.

#### INSTALLATION □

---

RIA-SA is designed for wall mounting. "Upside down" installation of the louvre is recommended to avoid see-through issues.

## TECHNICAL INFORMATION

### 1 Type

**RIA-SA** external weather louvres

### 2 Width [mm]

**200 - 2000**

### 3 Height [mm]

**200 - 2000**

### 4 Exposed surface

No entry: powder-coated, RAL 9003 (signal white)

**UL** without coating

**P1** powder-coated, specify RAL colour

**PS** powder-coated, specify NCS colour

**RIA-SA / 500 × 800 / P1 - RAL 9010**

| | | |  
1 2 3 4

Order example: RIA-SA/500×800/P1-RAL9010

Type	RIA-SA – external weather louvres
Width [mm]	500
Height [mm]	800
Exposed surface	powder-coated, RAL 9010 (pure white)

### Application

RIA-SA is an extract-air louvre ideal for high air flow rates

### Design

RIA-SA is made from extruded aluminium profiles.

### Materials and surface coating

RIA-SA is made from extruded, seawater resistant aluminium profiles (ENAW-6060-T66 / EN-AW-6063-T6), and comes in an RAL 9003 - gloss finish as standard. The unit can also be delivered in anodized brown, black or natural. Alternative materials or enamel finish are available on request.

### Installation

RIA-SA is designed for wall mounting. "Upside down" installation of the louvre is recommended to avoid see-through issues.

### Maintenance

Unit can be cleaned with a damp cloth.

### Environment

- Enquiries regarding product declaration can be directed to our sales team, or information can be found at our website: [www.trox.no](http://www.trox.no)