



# SIV-INN T/V

- Suitable for T-profile ceiling systemRemovable front
- Large capacity

**APPLICATION** 

Siv-inn T/V is a supply diffuser for areas requiring high air flow rates such as commercial kitchens or laboratories. Suitable for open as well as embedded installation (se fig. 2).

#### Design


The product is available in 6 different sizes, with circular end-spigot as standard. External dimensions are designed to fit T-profile ceiling systems with module 600. Alternative connection solutions and positioning are available on request. Siv-inn T/V can also be supplied with perforated sides. The front panel is reinforced and can be removed by unfastening the screws.

**DESCRIPTION** 

### **Materials and surfaces**

Siv-inn T/V comes in a galvanised steel-plate design. Sides and front are in a white RAL 9003 - gloss 30 finish.

## **TEKNISK INFORMATION**



Example: Siv-inn T/V-0612 / 0-0-0-0

Explanation: Siv-inn T/V, type: 0612 with spigot Ø250.



# QUICK SELECTION

Siv-inn T/V Type	[m³/h]		
	25 dB(A)	30 dB(A)	35 dB(A)
0312	230	300	430
0612	340	470	580
0618	540	680	860
1212	700	900	1200
1218	1000	1200	1600
1224	1200	1600	2000

Table 1: The table shows air flow rates at given sound power levels.